



## GENERAL SPECIFICATIONS

A mild steel automated rotor assembly with options of 3 or 4 arms, down lights, and rain canopy.

**DIMENSIONS:** Single 1410mm (w) x 1276mm (d) x 2225mm (h)  
Double 2785mm (w) x 1276mm (d) x 2225mm (h) All dims taken from top of 200mm deep concrete slab base.

**ROTOR:** 76mm Dia Tube.

**ARMS:** 42mm Dia Tube.

**SIDES:** 33mm Dia Tube welded to curved base plate.

**FLOW RATE:** 15 - 22 cycles per minute in single direction.

**CONTROL OPTIONS:** Keypad, Proximity cards, Video/Voice intercomm, Token acceptors, Remote fobs, Key switch.

**FINISH:** Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

**KEY FEATURES:** Provides a pedestrian access control solution which governs both direction and flow of access & egress through a secure perimeter. The NK 4000 Turnstile can also be integrated with industry standard access control systems & fire alarms.

\*All dimensions represent nominal values.

For further details on our complete automation range along with technical specifications, please visit our website at:

[www.nkfencing.com](http://www.nkfencing.com)

## RELATED PRODUCTS



### OTHER PRODUCTS:

- ▶ NK Sliding Gates
- ▶ NK Swinging Barriers
- ▶ NK Swinging Gates
- ▶ NK Bollards
- ▶ NK Rising Barriers
- ▶ NK Safety Gates

NK FENCING - Access control made simple

## STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK  
RAL 9005

GREY  
RAL 7037

BLUE  
RAL 5010

WHITE  
RAL 9010

GREEN  
RAL 6005

RED  
RAL 3000

YELLOW  
RAL 1006

BROWN  
RAL 8019