# **NKFENCING**

NK Fencing Lto (Head office)

40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU

t: +44 28 9335 1172

e: mail@nkfencing.com w: www.nkfencing.com

(Dublin depot)

6 Kylemore Business Park Kylemore Way Dublin 8 D08 ND00

t: +353 1 626 9000 e: mail@nkfencing.ie w: www.nkfencing.ie



### **GENERAL SPECIFICATIONS**

Cantilevered Sliding gate leafs of aluminium construction, driven by a powerful 3 phase electric motor with a 100% duty cycle. Rapid plug & play installation.

INFILL: Large range of infills available to compliment adjacent fencing.

AVAILABLE HEIGHTS: 1.2m, 1.8m, 2.0m, 2.4m and 3.0m#

AVAILABLE WIDTHS: 3m up to 12m per leaf in 500mm increments. If gates are of double leaf construction the available widths are twice the above.

OPERATION TIME: 4 seconds per metre (variable).

POWER UNIT: 3 phase motor.

STANDARD CONTROL: 1 Nr deadmans key switch on inner face of cabinet, 1 Nr Radio receiver and 2 Nr remote handheld transmitters.

STANDARD SAFETY: 6 Nr safety edges, dual height photocells mounted on the support structure, covering clear opening inside the gate leaf, flashing light.

KEY FEATURES: The NK 9000 Cantilever sliding gate guarantees smooth, consistent and quiet gate movement, along with the low maintenance rust free benefits of an aluminium product.

- \* All dimensions represent nominal values
- # Span limitations apply

A securely concealed manual release mechanism is included as standard allowing manual control of the gate in the event of a power failure. The controller is pre-configured to accept fire alarm feeds for emergency automated operation. The NK 9000 Cantilever sliding gate is fully compliant with BS EN 12453 safety features and is CE marked. Gates heights of 2.4m high or greater come complete as standard with a serrated top.

ADDITIONAL ITEMS: Control Options: Stainless steel Intercom, Stainless steel Videocom, Stainless steel key pad, Stand alone prox reader, Network prox reader and additional Hand held radio Transmitters.

For further details on our complete automation range along with technical specifications, please visit our website at:

www.fencing.com

# **RELATED PRODUCTS**

#### **OTHER PRODUCTS:**

- NK Swinging Gates
- NK Tracked Gates
- NK Traffic Barriers
- NK Safety Gates
- NK Swinging Barriers

NK FENCING - Access control made simple

## STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct

BLACK RAL 9005 GREY RAL 7037 BLUE RAL 5010 WHITE RAL 9010 GREEN RAL 6005

i Ri 05 RAL

RED RAL 3000 YELLOW RAL 1006 BROWN RAL 8019