



GENERAL SPECIFICATIONS

3 Arm or 4 Arm Rotor Assembly

SIZE: 1.2m x 1.4m x 2.2m high (2.3m high with canopy).

OUTER FRAME SURROUND: 25 x 25mm RHS vertical bar infill.

OR

60 x 100mm rectangular mesh comprising 6mm diameter horizontal round bar and 25 x 3mm vertical flat bars with 40 x 10mm top and bottom mild steel flat bar

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours to suit your individual requirements.

KEY FEATURES: Provides a pedestrian access control solution, channelling the entry/exit of people through the perimeter to a single point while simultaneously governing the flow of people accessing the secured area.

*All dimensions represent nominal values.

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK Sliding Gates
- ▶ NK Swinging Barriers
- ▶ NK Swinging Gates
- ▶ NK Bollards
- ▶ NK Rising Barriers
- ▶ NK Safety Gates

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019