



NK RISING BARRIERS

GENERAL SPECIFICATIONS

CONSTRUCTION: Cabinet - Steel, Beam - Aluminium, Hood - Fibreglass.

FINISH: Cabinet - Red (Corporate colours available upon request), Beam - Red/White.

DRIVE UNIT: Motor and Gearbox supplied by 240v Single Phase @ 50hz, 10 Amps.

MODEL	CABINET DIMENSIONS	POLE DIAMETER	BOOM LENGTHS (m)
Basic	1110x404x416mm	94x64mm	2m to 4m
Standard	1110x404x416mm	94x64mm	3m to 6m
Luxury	1110x404x416mm	94x64mm	4m to 7m
Hi-Definition	1120x455x490mm	123x84mm	4m to 9m

CONTROL OPTIONS: Card, Radio, Token, Keypad, Intercom, Push button, Vehicle transponder, Induction loop & Photocell.

ACCESSORIES: Corporate colours, Stop signs, Boom lights, PVC curtain skirt (half height only) and PVC high bars. Various end support posts and Card reader mounting posts.

*All dimensions represent nominal values.

KEY FEATURES: Offering vehicular access control or a single point security cordon. A compact access control solution available in either single leaf or double leaf configuration. All of our rising barriers come with integrated boom mounted safety edges. For further details on our complete automation range along with technical specifications, please visit our website at:

www.fencing.com

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK Sliding Gates
- ▶ NK Turnstiles
- ▶ NK Swinging Gates
- ▶ NK Bollards
- ▶ NK Swinging Barriers
- ▶ NK Safety Gates

NK FENCING - Access control made simple

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019