NKFENCING

(Head office)

40 Trailcock Road Carrickfergus Co. Antrim RT38 7NU

t: +44 28 9335 1172

w: www.nkfencing.com

(Dublin depot)

6 Kylemore Business Park **Kylemore Way Dublin 8** D08 ND00

t: +353 1 626 9000 e: mail@nkfencing.ie



GENERAL SPECIFICATIONS

Powered Cantilevered Sliding gate leafs of steel construction, driven by a powerful single phase electric motor with a 100% duty cycle.

INFILL: Large range of infills available including mesh, palisade & tubular railings.

AVAILABLE HEIGHTS: 1.2m, 1.8m, 2.0m, 2.4m #

AVAILABLE WIDTHS: 3m up to 10m per leaf in 500mm increments. If gates are of double leaf construction the available widths are twice the above.

OPERATION TIME: 4 seconds per metre (variable).

POWER UNIT: Single phase 10 Amp motor.

STANDARD CONTROL: Hold to run key switch.

STANDARD SAFETY: Dual height photocells mounted on the support structure, covering clear opening inside the gate leaf, flashing light & emergency stop button.

KEY FEATURES: The Steel Cantilever sliding gate guarantees smooth, consistent and quiet gate movement through a rack & pinion system controlled by an onboard programmable encoder. Movement is initiated with a hold to run key control by default, however additional controls with associated safety features are available on request.

All dimensions represent nominal values. Span limitations apply

A securely concealed manual release mechanism is included as standard allowing manual control of the gate in the event of a power failure. The controller can be pre-configured to accept fire alarm feeds for emergency automated operation. The Steel Cantilever sliding gate is CE marked in accordance with the Machinery Directive 2006/42/EC and is fully compliant with BS EN 13241-1: 2003 + A2: 2016. All of our gates are professionally installed with commissioning & testing to BS EN 12453: 2017. The Steel Cantilever Sliding Gate is designed to offer all the robustness & durability of a galvanised steel structure with the convenience of modern automated operation.

ADDITIONAL CONTROLS: Push button remote control, Key Fob reader, Mobile phone interface, Exit & Entry vehicle detection (ground buried induction loop), Keypad, Intercom, Videocom.

RELATED PRODUCTS

OTHER PRODUCTS:

- **Swinging Gates**
- **Swinging Barriers**
- **Tracked Sliding Gates**
- **Boom Barriers**
- Safety Gates
- **Aluminium Cantilever Gates**

NK ACCESS CONTROL - Automation made simple

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct

BLACK RAL 9005

GREY **RAL 7037**

BLUE **RAL 5010**

WHITE **RAL 9010**

GREEN RAL 6005

RED **RAL 3000**

YELLOW **RAL 1006**

BROWN **RAL 8019**