

NK AUTOMATION

NK Fencing Ltd
(Head office)
40 Trailcock Road
Carrickfergus
Co. Antrim
BT38 7NU
t: +44 28 9335 1172
f: +44 28 9336 4336
e: mail@nkfencing.com
w: www.nkautomation.co.uk

(Dublin depot)
Backweston
Leixlip
Co. Dublin
Ireland
t: +353 1 626 9000
f: +353 1 624 5465
e: mail@nkfencing.ie
w: www.nkautomation.ie

NK AUTO TURNSTILE



GENERAL SPECIFICATIONS

3 Arm Automated Rotor Assembly with optional canopy.

DIMENSIONS: 1480mm x 1410mm x 2350mm (+ 60mm)

ROTOR: 76mm Dia Tube.

ARMS: 42mm Dia Tube.

SIDES: 33mm Dia Tube welded to curved base plate.

FLOW RATE: 15 - 22 cycles per minute in single direction.

CONTROL OPTIONS: Keypad, Proximity cards, Video/
Voice intercomm, Token acceptors, Remote fobs, Key switch.

FINISH: Galvanised and polyester powder coated to BS
EN 13438-2005 in a range of colours to suit your individual
requirements.

KEY FEATURES: Provides a pedestrian access control solution
which governs both direction and flow of access & egress
through a secure perimeter. PLC controlled with hidden
cabling, the NK Auto Turnstile seamlessly integrates with
industry standard access control systems.

*All dimensions represent nominal values.

For further details on our complete automation range along with
technical specifications, please visit our website at:

www.nkautomation.co.uk

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK Sliding Gates
- ▶ NK Swinging Barriers
- ▶ NK Swinging Gates
- ▶ NK Bollards
- ▶ NK Rising Barriers
- ▶ NK Safety Gates

NK AUTOMATION - Access control made simple

STANDARD COLOUR RANGE

The colours shown are indicative colours. No
guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019

NK Automation is a trading name of NK Fencing Ltd and has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier.
Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.