NKFENCING

(Head office)

40 Trailcock Road Carrickfergus Co. Antrim **BT38 7NU**

t: +44 28 9335 1172 f: +44 28 9336 4336

e: mail@nkfencing.com

(Dublin depot)

Backweston Leixlip Co. Dublin Ireland

t: +353 1 626 9000 f: +353 1 624 5465



GENERAL SPECIFICATIONS

POST SYSTEM: RHS posts at 2.950m centres, panel fixed to posts with 25 x 5mm slotted clamp bar using NK M8 tamper-resistant bolt and threaded nutserts.

PANEL WIDTH: 3m

MESH APERTURE: 200mm x 25mm

WIRE DIAMETER: 5mm horizontal, 5mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION	NUMBER OF FOLDS	NUMBER OF FIXINGS
1.2	60x60	2	4
1.8#	60x60	3	4
2.4	60x60	3	5
3.0#*	60x60	5	8

* Multi-lift panels - 1.8 with 1.2 above. Panels must be installed wire ends down, to ground level.

APPLICATION: NK Ibex Elite Plus is a general purpose fencing system for boundary demarcation and aesthetic perimeters. It is widely used in commercial and public sector buildings where a uniform and solid facade is desired. All dimensions represent nominal values.

KEY FEATURES: NK Ibex Elite Plus utilises a high density rigid mesh panel with a 200 x 25mm mesh aperture offering enhanced security - thereby making scaling difficult.

Panels taller than 1.2m offer 21mm protruding wire ends on the top edge to provide an increased security enhancement. In all instances where fence heights are below 2m, panels must be installed wire ends down and embedded at ground level. Installation of all fencing is subject to site specific risk assessments and NK recommends due regard should be given to nearby aids to scaling or natural overhangs.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either with manual or automated control.

OTHER PRODUCTS:

- NK Ibex Elite
- NK Ibex Eco Plus
- NK Ibex Supreme 656
- NK Ibex Eco

- NK Ibex Supreme 868
- **NK Ibex Safetop**

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct

BLACK RAL 9005

GREY RAL 7037

BLUE **RAL 5010**

WHITE **RAL 9010**

GREEN RAL 6005

RED **RAL 3000**

YELLOW **RAL 1006**

BROWN **RAL 8019**