

GENERAL SPECIFICATIONS

POST SYSTEM: RHS at 2.440m centres, panel fixed to posts with 40 x 6mm slotted clamp bar.

PANEL WIDTH: 2.5m

MESH APERTURE: 76.2mm x 12.7mm

WIRE DIAMETER: 4mm horizontal, 4mm vertical.

FINISH: Available galvanised or galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION RHS	NUMBER OF FIXINGS	FIXING TYPE
2.10	60x60	8	NK M8 tamper-resistant bolts and threaded nutserts
2.40	60x60	9	NK M8 tamper-resistant bolts and threaded nutserts
2.70	80x80	10	NK M8 tamper-resistant bolts and threaded nutserts
3.00	80x80	11	NK M8 tamper-resistant bolts and threaded nutserts
3.60	100x100	13	NK M8 tamper-resistant bolts and threaded nutserts
4.20	100x100	15	NK M8 tamper-resistant bolts and threaded nutserts
5.20	100x100	18	NK M8 tamper-resistant bolts and threaded nutserts

* All dimensions represent nominal values.

KEY FEATURES: A high density wire mesh perimeter fencing system, offering a strong visual deterrent and physical protection with an anti-climb mesh aperture. NK Ibex Security robustly protects while maintaining the pleasing aesthetics of rigid mesh fencing.

RELATED PRODUCTS



AUTOMATED GATES: NK Automated Cantilever Sliding Gate (see specific brochure).

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements.

OTHER PRODUCTS:

- ▶ NK Ibex Vogue
- ▶ NK Ibex Elite
- ▶ NK Ibex Supreme 868
- ▶ NK Ibex Hi-Security
- ▶ NK Ibex Premier Plus
- ▶ NK Ibex Premier

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019