



NK IBEX

GENERAL SPECIFICATIONS

POST SYSTEM: RHS at 2.523m centres, panel fixed to posts with type 656 clips using NK M8 tamper-resistant bolt with threaded nutserts.

PANEL WIDTH: 2.5m

MESH APERTURE: 200 x 50mm

WIRE DIAMETER: 6mm horizontal, 5mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTIONS RHS	NUMBER OF FIXINGS
1.2*	60x60	4
1.8*	60x60	6
2.0	60x60	6
2.4	60x60	7

* Panels must be installed wire ends down, to ground level.

APPLICATION: NK IbeX Supreme 656 is a heavy duty rigid mesh fencing system for boundary demarcation and aesthetic perimeters where increased security and resilience to damage is needed. NK IbeX Supreme 656 is a popular choice for industrial centres, commercial premises and business parks. All dimensions represent nominal values.

KEY FEATURES: NK IbeX Supreme 656 is constructed from a heavy duty rigid mesh panel with a 200mm x 50mm mesh aperture having thick horizontal wires 6mm diameter and single vertical wire 5mm diameter. Panels offer 21mm protruding wire ends on the top edge to provide an increased security enhancement. In all instances where fence heights are below 2m, panels must be installed wire ends down and embedded at ground level. Installation of all fencing is subject to site specific risk assessments and NK recommends due regard should be given to nearby aids to scaling or natural overhangs.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or with automated control.

OTHER PRODUCTS:

- ▶ NK IbeX Supreme 868
- ▶ NK IbeX Elite Plus
- ▶ NK IbeX Elite
- ▶ NK IbeX Eco Plus
- ▶ NK IbeX Eco Plus
- ▶ NK IbeX Safetop

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019