



GENERAL SPECIFICATIONS

FENCING SYSTEM: RHS posts at 2.523m centres, panel fixed to posts with type 656 clips using NK M8 tamper-resistant bolt with threaded nutserts. Printed PES membrane fabric inserts are woven into the mesh panel to form a solid privacy screen.

PANEL WIDTH: 2.5m

PANEL MESH APERTURE: 200 x 50mm

WIRE DIAMETER: 6mm horizontal, 5mm vertical.

FINISH: Galvanised and polyester powder coated Black to BS EN 13438.

FENCE Ht (m)	POST SECTIONS RHS	NUMBER OF FIXINGS
1.8	60x60	6
2.0	60x60	6
2.4	60x60	7

APPLICATION: The NK Privacy fence is a hybrid rigid mesh fencing system for boundary demarcation and aesthetic perimeters where privacy and uniqueness is valued. NK Privacy fencing is a popular screening choice for commercial premises and business parks.

* All dimensions represent nominal values.

KEY FEATURES: NK Privacy fencing is constructed from a heavy duty rigid mesh panel with a 200mm x 50mm mesh aperture having thick horizontal wires 6mm diameter and single vertical wire 5mm diameter. Panels offer 22mm protruding wire ends on the top edge to provide an increased security enhancement. Installation of all fencing is subject to site specific risk assessments and for heights less than 2m, NK recommends the panels are installed with the protruding wire ends pointing down and embedded. Printed waterproof fabric is constructed from a UV resistant Polyethersulfone (PES) membrane.

RELATED PRODUCTS

SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, with manual or with automated control.

OTHER PRODUCTS:

- ▶ NK IbeX Supreme
- ▶ NK IbeX Elite
- ▶ NK IbeX Eco
- ▶ NK IbeX Security
- ▶ NK IbeX Hi-Security
- ▶ NK Acoustic Type-R

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019