



NK RAILINGS

GENERAL SPECIFICATIONS

HEIGHT: 2.1m (additional heights/specification available on request).

POST SYSTEM: 80 x 40mm RHS at 2.5m centres.

VERTICAL INFILL: 25mm diameter ERW vertical bars at 125mm centres.

FINISH: Galvanised and polyester powder coated to BS EN 13438-2005 in a range of colours.

KEY FEATURES: With optional crush style designs available thus providing the opportunity to create your own unique patterns to enhance the perimeter with an elite railing system. Twinned top and bottom rails gives added strength and rigidity with additional benefit of creating articulated panels to suit sloped site conditions.

Full CAM brochure available on request
OR Visit the CAM Website: www.cam-ltd.co.uk

RELATED PRODUCTS



SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either manual or with automated control.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK Traditional Railings
- ▶ NK Blackstaff Railings
- ▶ NK Industrial Railings
- ▶ NK Pedestrian Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019