



GENERAL SPECIFICATIONS

HEIGHT: 1.22m.

POST DETAIL: 40 x 10mm flat bar, with 3 nbr M8 x 30 cup square bolts and permacone anti-vandal nuts.

RAILING DETAIL: 20mm diameter top horizontal round bar and 4 nbr 25 x 6mm flat bar horizontals having the 25mm face to view.

FINISH: Galvanised and polyester powder coated to BS EN 1461 & BS EN 13438 in a range of colours to suit your individual requirements.

KEY FEATURES: A traditional and minimalistic design. The railing system is particularly suitable for land demarcation & rural themed housing developments.

*All dimensions represent nominal values.

RELATED PRODUCTS



SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either with manual or automated control.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK CAM railings
- ▶ NK Industrial Railings
- ▶ NK Traditional Railings
- ▶ NK Bespoke Railings
- ▶ NK Housing Railings

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019