

NK RAILINGS

GENERAL SPECIFICATIONS

HEIGHT: 0.6m, 0.9m, 1.1m, 1.2m.

POST DETAIL: 40 x 40mm RHS, 4 No M10 cup square and permacone anti vandal fixing to railing and 4 No M8 power drive fixing to posts at 3052mm centres.

PANEL DETAIL: 30x10 flat bar top and bottom rail and 12mm round bar infill, verticals at 112mm crs (100mm gap).

OPTIONS: Standard post, end post and corner posts. Panel topping options include, Bow top, Plain top and Under top rail

FINISH: Galvanised and polyester powder coated to BS EN 1461-2009 & BS EN 13438-2005 in a range of colours to suit your individual requirements.

KEY FEATURES: Attractive and robust railing system suitable for housing developments. Standard system offers rapid & simplified installation with minimal tooling requirements.

*All dimensions represent nominal values.

RELATED PRODUCTS



SWINGING AND SLIDING GATES: Single Leaf Swinging Gates are available in a range of standard widths to suit your individual requirements.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK CAM railings
- ▶ NK Bespoke Railings
- ▶ NK Industrial Railings
- ▶ NK Ranch Railings
- ▶ NK Traditional Railings

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019