NKFENCING

(Head office)

40 Trailcock Road Carrickfergus Co. Antrim **BT38 7NU**

t: +44 28 9335 1172 +44 28 9336 4336

e: mail@nkfencing.com w: www.nkfencing.com Ireland t: +353 1 626 9000 f: +353 1 624 5465

(Dublin depot) Backweston

Leixlip Co. Dublin

e: mail@nkfencing.ie



GENERAL SPECIFICATIONS

HEIGHT: 1.22m.

POST DETAIL: 40 x 10mm flat bar, with 3 nbr M8 x 30 cup square bolts and permacone anti-vandal nuts.

RAILING DETAIL: 20mm diameter top horizontal round bar and 4 nbr 25 x 8mm flat bar horizontals having the 25mm face to view.

FINISH: Galvanised and polyester powder coated to BS EN 1461 & BS EN 13438 in a range of colours to suit your individual requirements.

KEY FEATURES: A traditional and minimalistic design. The railing system is particularly suitable for land demarcation & rural themed housing developments.

*All dimensions represent nominal values.

RELATED PRODUCTS



SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either with manual or automated control.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- **NK CAM railings**
- **NK Bespoke Railings**
- **NK Industrial Railings**
- NK Pedestrian Guard Rail
- **NK Traditional Railings**

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct

BLACK RAL 9005

GREY RAL 7037

BLUE **RAL 5010**

WHITE **RAL 9010**

GREEN RAL 6005

RED **RAL 3000**

YELLOW **RAL 1006**

BROWN **RAL 8019**