



NK RAILINGS

GENERAL SPECIFICATIONS

HEIGHT: 1m, 1.2m, 1.8m, 2m.

POST DETAIL: 50 x 50mm RHS, 4 times cleated to receive panels, maximum post enters 3000mm. Section increases to 80 x 80mm RHS at heights of 1.8m or above.

PANEL DETAIL: 50 x 10mm flat bar top and bottom horizontal rails with 16mm diameter verticals at 110mm centres forming bowtop or alternative plain or cone top. Infill increases to 20mm diameter verticals at heights of 1.8m or above.

OPTIONS: Other heights/specifications available on request, including Cone top, Square top & Hoop top.

FINISH: Galvanised and polyester powder coated to BS EN 1461-2009 & BS EN 13438-2005 in a range of colours to suit your individual requirements.

KEY FEATURES: Attractive and robust railing system suitable for play areas, parks and housing developments.

*All dimensions represent nominal values.

RELATED PRODUCTS



SWINGING AND SLIDING GATES: Single and Double Leaf Swinging and Sliding Gates are available in a range of standard widths to suit your individual requirements, either with manual or automated control.

SAFETY GATES: NK Self Closing single leaf gate (see specific brochure).

OTHER PRODUCTS:

- ▶ NK CAM railings
- ▶ NK Industrial Railings
- ▶ NK Decorative Railings
- ▶ NK Bespoke Railings
- ▶ NK Pedestrian Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019