



NK GUARD RAIL

GENERAL SPECIFICATIONS

HEIGHT: 1m above ground level.

WIDTH: 1.8m

STANDARD PANEL DETAIL: 50 x 30mm RHS frame, having top and bottom rails drilled for 15 nbr 12mm round bar vertical infill inserts, fully welded at 112mm centres. Adjacent panels are bolted together with 2 nbr M10 x 80mm bolts, nuts and nylon washers.

FINISH: Galvanised to BS EN 1461-2009.

KEY FEATURES: A National Roads Authority approved railing system, widely in use throughout the Republic of Ireland road network, suitable for roadside pedestrian marshalling. Typical applications include along roadways, road crossings and access points.

*All dimensions represent nominal values.

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK CAM Railings
- ▶ NK Acoustic Barriers
- ▶ NK Crash Barriers
- ▶ NK On Road Guardrail
- ▶ NK Off Road Guardrail
- ▶ NK Standard Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.



BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019