



NK GUARD RAIL

GENERAL SPECIFICATIONS

OPTIONS: Standard or Vision Panel.

HEIGHT: 1m above ground level.

POST DETAIL: 50 x 50mm RHS set at 1520mm centres with 40 x 40mm RHS connecting spigots with M10 x 30mm long cadmium screw sets to the top horizontals and M10 x 30 countersunk cadmium screw sets to flat bar.

STANDARD PANEL DETAIL: 50 x 50mm RHS horizontal top rail and 40 x 10mm flat bar bottom rail with 20mm round bar vertical infill at 123mm centres.

VISION PANEL DETAIL: 50 x 50mm RHS horizontal top rail, 40 x 10mm flat bar middle and bottom rails with 20mm round bar vertical infill at 123mm centres.

FINISH: Galvanised to BS EN 1461-2009.

KEY FEATURES: A Government approved railing system, fully **performance certified** in accordance with BS 7818, suitable for roadside pedestrian marshalling. Typical applications include along roadways, road crossings and access points.

*All dimensions represent nominal values.

RELATED PRODUCTS



OTHER PRODUCTS:

- ▶ NK CAM Railings
- ▶ NK Acoustic Barrier
- ▶ NK Crash Barrier
- ▶ NK Hazard Guard Rail
- ▶ NK NRA Spec Guard Rail
- ▶ NK Standard Guard Rail

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019