## **NKFENCING**

NK Fencing Ltd (Head office) 40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU t: +44 28 9335 1172 e: mail@nkfencing.com

w: www.nkfencing.com

(Dublin depot) 6 Kylemore Business Park Kylemore Way Dublin 8 D08 ND00 t: +353 1 626 9000 e: mail@nkfencing.ie w: www.nkfencing.ie



## **GENERAL SPECIFICATIONS**

POST SYSTEM: SHS posts at 2.523m centres, fixed to posts with NK clip Type 868 using NK Stainless Steel M8 microencapsulated vibration and tamper-resistant bolt and threaded nutserts.

PANEL WIDTHS: 2500mm

MESH APERTURE: 200 x 50mm.

WIRE DIAMETER: Twin 8mm horizontal, single 6mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

NOISE REDUCTION: We can offer additional neoprene strips between post and panel. This can reduce noise by up to 29%.

NOMINAL Ht (m)	POST SECTIONS SHS	NUMBER OF FIXINGS	MESH PANEL CONFIGURATION
3.0	70x70x3	9	3000mm
4.2	80x80x3	13	3000mm&1200mm
5.0	100x100x3	15	3000mm&2000mm
5.5	100x100x4	16	3000mm&2500mm
6.0	100x100x4	17	3000mm&3000mm

## \*All dimensions refer to nominal values.

When compared against BS1722 Part 14 Table 2, this fencing system has a solidity rating of 16 % with an application rating of 'security'.

KEY FEATURES: Ballstop system offering a 3.0m high heavy duty rigid mesh panel, comprising of 200mm x 50mm mesh apertures, having twin horizontal wires 8.0mm diameter and single vertical wire 6.0mm diameter, vertical wires protrude 25mm above top horizontal wire. The system offers a rigid, durable and safe system for optimum sports performance with a unique uniform appearance.



NK Sports Pitch Surround: A 1.2m pitch surround solution to compliment our ballstop systems. NK Sports Pitch Surround can be further enhanced with gates and integrated dugouts.

NK Sports Tennis Courts

## **OTHER PRODUCTS:**

- NK Sports Ballcatch
  - NK Sports Protection Net

STANDARD COLOUR RANGE								
The colours shown are indicative colours. No guarantee can be given that the match is correct.	BLACK	GREY	BLUE	WHITE	GREEN	RED	YELLOW	BROWN
	RAL 9005	RAL 7037	RAL 5010	RAL 9010	RAL 6005	RAL 3000	RAL 1006	RAL 8019

NK Fencing has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier. Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.