NKFENCING

NK Fencing Ltd (Head office) 40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU t: +44 28 9335 1172 e: mail@nkfencing.com w: www.nkfencing.com

(Dublin depot) 6 Kylemore Business Park Kylemore Way Dublin 8 D08 ND00 t: +353 1 626 9000 e: mail@nkfencing.ie w: www.nkfencing.ie



GENERAL SPECIFICATIONS

POST SYSTEM: SHS posts at 2.523m centre, fixed to posts with NK Clip Type 868 and NK M8 microencapsulated vibration and tamper-resistant bolt and threaded nutserts..

PANEL WIDTH: 2.5m

MESH APERTURE: Lower Panel – 50x65 for bottom 1000mm, 50x100 for middle 1000mm, 50x200 for upper 1000mm.

WIRE DIAMETER: Double Wire = 8mm horizontal, 6mm vertical, 8mm horizontal

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

NOISE REDUCTION: We can offer additional neoprene strips between post and panel. This can reduce noise by up to 29%.

NOMINAL Ht (m)	POST SECTION SHS	NUMBER OF FIXINGS	MESH PANEL CONFIGURATION		
2.4	70x70x3	7	2430mm		
3.0	70x70x3	9	3030mm		
4.2	90x90x3	13	3030mm & 1230mm		
5.0	100x100x3	15	3030mm & 2030mm		
5.5	100x100x4	16	3030mm & 2430mm		
6.0	100x100x4	18	3030mm & 3030mm		

KEY FEATURES: A double wire rigid mesh ballstop system featuring a unique 3.0m high panel with a diverging aperture integrated rebound area (50x65:50x100:50x200). Upper sections of the system are formed using 50x200 mesh with NK Ibex Supreme 868 panels. The NK Sports Ballstop 3D is recommended for Multi-Use Games Areas (MUGAs) and hard ball sports environments, where the fencing is erected on the edge of the pitch or court, thus offering minimum run off and presenting high impact zones.



The NK Sports Protection Net is an optional enhancement available on all NK Sports Ballstop systems. A nylon net is suspended 500mm from the face of the fence offering a high impact resistant area along with an energy absorbing surface to reduce ball speed & rebound.

*All dimensions represent nominal values.

NB: Where hockey is to be played we would recommend the inclusion of a softwood timber kickboard, 225 x 35mm chamfered one edge, fitted to the base of the fencing.

STANDARD COLOUR RANGE								
The colours shown are indicative colours. No guarantee can be given that the match is correct.	BLACK	GREY	BLUE	WHITE	GREEN	RED	YELLOW	BROWN
	RAL 9005	RAL 7037	RAL 5010	RAL 9010	RAL 6005	RAL 3000	RAL 1006	RAL 8019

NK Fencing has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier. Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.