NKFENCING

(Head office) 40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU t: +44 28 9335 1172 e: mail@nkfencing.com w: www.nkfencing.com

6 Kylemore Business Park **Kylemore Way** Dublin 8 D08 ND00 t: +353 1 626 9000 w: www.nkfencing.ie



GENERAL SPECIFICATIONS

POST SYSTEM: SHS posts at 2.523m centres, mesh fixed to posts with NK Clip Type 868 using NK Stainless Steel M8 microencapsulated vibration and tamper resistant bolt and threaded nutserts. Netting support and straining post sections 100x100 SHS to full height, intermediate post section 70x70 SHS to panel height.

PANEL DIMENSIONS: Width: 2.5m, Height: 3.0m.

MESH APERTURE: 50 x 200mm.

WIRE DIAMETER: Double wire = 8mm horizontal, 6mm vertical, 8mm horizontal.

NET HEIGHT: Available in heights of 2, 3 and 4m.

NET APERTURE: 50mm aperture, 2.3mm diameter.

FINISH: Posts and panels galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements. Polyethylene UV resistant knotted sport netting available in black or green.

KEY FEATURES: NK Sports Combi is a hybrid ball court fencing system comprising of a rigid steel mesh rebound perimeter fence, topped with an integrated polyethylene ball retention netting system. The NK Sports Combi offers an environmentally kind low carbon sports system, best suited for use within secure perimeters & areas where there is a low risk to vandalism.



NK SPORTS BALLSTOP 2D/3D: A double wire rigid mesh ballstop system featuring a unique 3m high panel with a diverging aperture integrated rebound area. Recommended for Multi-Use Games Areas (MUGAs).

OTHER PRODUCTS:

- NK Sports Ballstop
- NK Sports Tennis Courts
- NK Sports Ballstop 2D/3D NK Sports Ballcatch Net
- NK Sports Pitch Surround
 NK Sports Protection Net

*All dimensions represent nominal values.

STANDARD COLOUR RANGE								
The colours shown are indicative colours. No guarantee can be given that the match is correct.	BLACK	GREY	BLUE	WHITE	GREEN	RED	YELLOW	BROWN
	RAL 9005	RAL 7037	RAL 5010	RAL 9010	RAL 6005	RAL 3000	RAL 1006	RAL 8019

NK Fencing has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier. Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.