NKFENCING

NK Fencing Ltd (Head office) 40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU t: +44 28 9335 1172 e: mail@nkfencing.com w: www.nkfencing.com

(Dublin depot) 6 Kylemore Business Park Kylemore Way Dublin 8 D08 ND00 t: +353 1 626 9000 e: mail@nkfencing.ie w: www.nkfencing.ie

NKSPORTS

GENERAL SPECIFICATIONS

SYSTEM: NK Sports Pitch Surround is a 'Red Guide' compliant pitch surround designed for the purpose of playing field demarcation. Please refer to type classifications in Chapter 10, Pitch Surrounds, of "The Northern Ireland Guide to Safety at Sports Grounds" as issued by Department of Culture, Arts and Leisure.

POST SYSTEM: RHS posts at 2.538m centres, mesh fixed to posts and rails with NK Clip Type 009, all comprising of NK M8 microencapsulated vibration and tamper-resistant bolt and threaded nutserts.

PANEL WIDTH: 2.5m.

MESH APERTURE: 76.22mm x 12.70mm.

WIRE DIAMETER: 4mm horizontal, 4mm vertical.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

KEY FEATURES: A high density rigid wire mesh pitch surround system to compliment our NK Sports Impact perimeter ballstop solution. Pitch surrounds can be further enhanced with access gates, integrated dugouts and advertising hoardings as required.

NB: Where hockey is to be played we would recommend the inclusion of a softwood timber kickboard, 225 x 35mm chamfered one edge, fitted to the base of the fencing. * All dimensions represent nominal values.



SWINGING GATES: Single and Double Leaf Gates are available in a range of standard widths.

OTHER PRODUCTS:

- NK Sports Ballstop 2D/3D NK Sports Ballcatch
 - INK Sports Ballcatch
- NK Sports Retractable Divider Net
- NK Sports Protection Net
- NK Sports Tennis Courts



NK Fencing has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier. Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.