NKFENCING

NK Fencing Ltd (Head office) 40 Trailcock Road Carrickfergus Co. Antrim BT38 7NU t: +44 28 9335 1172 e: mail@nkfencing.com

w: www.nkfencing.com

(Dublin depot) 6 Kylemore Business Park Kylemore Way Dublin 8 D08 ND00 t: +353 1 626 9000 e: mail@nkfencing.ie w: www.nkfencing.ie



GENERAL SPECIFICATIONS

SYSTEM: NK Sports Pitch Surround Plus is a 'Red Guide' compliant pitch surround designed for the purpose of playing field demarcation. Please refer to type classifications in Chapter 10, Pitch Surrounds, of "The Northern Ireland Guide to Safety at Sports Grounds" as issued by Department of Culture, Arts and Leisure.

POST SYSTEM: 60 x 60 RHS posts at 2.523m centres (resistance to bending 8.30cm3). Mesh fixed to posts and rails with NK clip type 868, all comprising of NK stainless steel M8 microencapsulated vibration and tamper-resistant bolt and threaded nutserts.

PANEL: Width = 2.5m, Height = 1.2m.

MESH APERTURE: 66mm x 50mm.

WIRE DIAMETER: Double wire = 8mm horizontal, 6mm vertical, 8mm horizontal.

FINISH: Galvanised and polyester powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

KEY FEATURES: A double wire rigid mesh spectator fencing system to compliment our NK Sports Ballstop 2D or 3D perimeter solution. Spectator fencing can be further enhanced with access gates, integrated dugouts and advertising hoardings as required.

* All dimensions represent nominal values.



SWINGING GATES: Single and Double Leaf Gates are available in a range of standard widths.

OTHER PRODUCTS:

- NK Sports Ballstop 3D
- NK Sports Ballstop 2D
- NK Sports Ballstop
- NK Sports Rebound
- NK Sports Pitch Surround
- NK Sports Pitch Surround Impact

NB: This product is suitable for frequent use soft ball sports facilities such as 3G soccer pitches. Where hockey is to be played we would recommend the use of the NK Sports Pitch Surround Impact system.

STANDARD COLOUR RANGE								
The colours shown are indicative colours. No guarantee can be given that the match is correct.	BLACK	GREY	BLUE	WHITE	GREEN	RED	YELLOW	BROWN
	RAL 9005	RAL 7037	RAL 5010	RAL 9010	RAL 6005	RAL 3000	RAL 1006	RAL 8019

NK Fencing has a policy of continuous innovation and as a result specification may change without notice. Suitability of use and design remain the responsibility of the specifier. Please refer to our terms & conditions of quotation & contract, care and maintenance instructions, and all technical information as provided on our website and available on request.