



## GENERAL SPECIFICATIONS

| FENCE HT (m)                                 | 0.9   | 1.2   | 1.5   | 1.8   | 2.15  | 2.4   |
|--|-------|-------|-------|-------|-------|-------|
| POST SECT (mm)                               | 40x40 | 40x40 | 40x40 | 40x40 | 40x40 | 50x50 |
| LINE WIRES                                   | 2     | 3     | 3     | 3     | 3     | 4     |
| MESH APERTURE                                | 50x50 | 50x50 | 50x50 | 50x50 | 50x50 | 50x50 |
| MESH GAUGES (mm) - GALVANISED                |       |       |       |       |       |       |
| 2.5  | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| 3.0  | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| 3.55   | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| MESH GAUGES (mm) - GALVANISED AND PVC COATED |       |       |       |       |       |       |
| 2.24/3.15                                    | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| 2.5/3.55                                     | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| 3.0/4.0                                      | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |
| 3.55/4.75                                    | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |

**FINISH:** Galvanised or galvanised and PVC coated green or black.

\*All dimensions represent nominal values.

**KEY FEATURES:** A well proven economic versatile and easy to erect fencing system. No exact post centres are required, making it ideal for re-clads on existing posts. Suitable in situations where minimal perimeter security is required.

## RELATED PRODUCTS



**GATES:** Single and Double Leaf Gates in a range of widths with NK Type 1A adjustable hinges and NK Type 2A latch.

► Weldmesh

► Salvus Safety Gate

## STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK  
RAL 9005

GREY  
RAL 7037

BLUE  
RAL 5010

WHITE  
RAL 9010

GREEN  
RAL 6005

RED  
RAL 3000

YELLOW  
RAL 1006

BROWN  
RAL 8019